

# BRADEN

## PD17A-47064-27G

### Features and Benefits

- Free fall (available on some units)
- Groove drum to help prevent spooling issues (available on some units)
- Multiple drum sizes available
- Overrunning clutch
- Single or two-speed motors available
- Spring-applied multi-disc brake
- Tension roller kit to help prevent spooling issues (available on some units)



Line Pull	Unit Weight
16070lbs	0lbs
7289kg	0kg

### Performance

	Imperial	Metric
Ratio	47.000:1	
Motor Displacement	6.380 ci	104.6 cc
Pressure	2999 psi	207.0 bar
Winch Flow	80 gpm	302.9 lpm
Rope Diameter	0.7500 in	19.1 mm
Cable Capacity	207 in	63 mm

Layer	Line Pull (lbs)	Line Speed (fpm)	Line Pull (kg)	Line Speed (mpm)
1	16070	207	7289	64
2	14490	230	6573	71
3	13190	253	5983	78
4	12110	276	5493	85
5	11190	298	5076	91

The last legal layer per ANSI is 5  
D/d = 18:1

### Applications for MODEL PD17

- Crane
- Utility
- Offshore

#### Resources:

- [Sales - LIT2077](#)
- [Sales - LIT2078](#)
- [Sales - LIT2446](#)
- [Service - LIT2103](#)
- [Material List - LIT2099](#)
- [Material List - LIT2137](#)
- [Material List - LIT2241](#)