

## Specifications

<b>Rated Line Pull</b>	<i>8,000 Lbs / 3,629 Kg</i>
<b>Note</b>	<i>Rated line pull is based on the first layer of cable. Rated line speed is based on cable with No Load.</i>
<b>1st Layer Line Speed</b>	<i>20 Ft/Min / 6.1 M/Min</i>
<b>Gear Ratio</b>	<i>360:1</i>
<b>Weight w/o Cable</b>	<i>130 Lbs / 59 Kg</i>
<b>Brake</b>	<i>Yes – brake is self-locking</i>
<b>Cable</b>	<i>Includes Cable</i>
<b>Drum Size (L x F x B)</b>	<i>8.25 x 7.25 x 3.50 In / 209.6 x 184.2 x 88.9 MM</i>
<b>Cable Capacity</b>	<i>150 Ft / 45.7 M</i>
<b>Recommend Cable Size</b>	<i>5/16 In / 7.9 MM</i>
<b>Motor Output</b>	<i>2.5 HP, 4.8 HP</i>
<b>Motor Size</b>	<i>Series Wound</i>
<b>Voltage</b>	<i>12V, 24V</i>
<b>Fairlead</b>	<i>Hawse, Roller</i>
<b>Clutch Type</b>	<i>RAM-LOK®</i>
<b>Clutch Control</b>	<i>Manual</i>