



# RAMSEY WINCH

## DC 34.9



- Rated Line pull 34.9 kN
- Recommended cable 10 mm
- Motor spool directional control valve required
- Standard air shift
- EN 14492-1 Compliant
- Made in the USA

### DC 34.9 Features

- Spring applied, hydraulic released multi disc brake
- High efficiency planetary gear set
- Foot mount or mid mount
- Fairlead and cable tension optional
- Manual or air operated free spool

### Applications

- Towing & Recovery
- Petroleum
- Forestry
- Mining
- Construction
- Refuse

### Specifications

LAYER OF ROPE		1	2	3
*RATED LINE PULL PER LAYER	kN	34.9	28.9	24.9
CUMMULATIVE ROPE CAPACITY PER LAYER (LONG DRUM)	M.	7	16	28
CUMMULATIVE ROPE CAPACITY PER LAYER (SHORT DRUM)	M.	3	9	15

LINE PULL FIRST LAYER	kN	No Load	8.8	17.7	34.9
*DC 34.9 & DCY 34.9 LINE SPEED FIRST LAYER 12V & 24V	MPM	4.3	2.1	1.5	1.7
*DC 34.9 & DCY 34.9 AMP DRAW	12V 24V	65 30	110 50	180 90	370 140

\* These specifications are based on recommended wire rope of 10 mm 1960 grade wire rope.

### Winch Dimensions

WINCH MODEL	A INCHES MM	B INCHES MM	C INCHES MM	D INCHES MM
DC 34.9	7.78 197.6	11.31 287.3	8.94 227.0	13.12 333.3
DCY 34.9	5.28 134.1	6.31 160.3	11.44 290.5	8.12 206.3

